

Product Number: IPEX1-IPEX4-0.5M
Product Name: Coaxial Cable


Index:

- 1. Specification**
- 2. Characteristics and Reliability Test**
- 3. Mechanical Drawing**

Product Number: IPEX1-IPEX4-0.5M

Product Name: Coaxial Cable

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency	DC 3 GHz
Impedance	50 Ohm
V.S.W.R.	<=2.0
Insertion Loss	<= -2.5dB
Voltage (breakdown)	> 500V
B. Material & Mechanical Characteristics	
Material of Conductor	Cu
Connector Type	IPEX
Pull Test of Mini Connector	>= 1 Kg
Mating Cycles	> 500
C. Environmental	
Operation Temperature	- 40 °C ~ + 65 °C
Storage Temperature	- 40 °C ~ + 80 °C

Product Number: IPEX1-IPEX4-0.5M

Product Name: Coaxial Cable



2. Characteristics and Reliability Test

Test Items		Test Condition and Procedure	Requirements	Result
C1	V.S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification	PASS
C2	Insertion Loss	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification	PASS
M4	Pull Test	Holding with individual specification; force applied to axis of terminal .	1. Directive DUT specification 2. Frequency Tol.≤5%	PASS
M6	Dimension	Inspection of dimension, color, material, package, surface process.	Directive DUT specification	PASS
E2	Salt Spray	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 24H	1. No Visual Damage 2. Frequency Tol.≤5%	PASS
E3	Temperature and Humidity Chamber	GB / T 2423.3-2006 Temp: 80°C / 12 H; -40°C / 12H RH: ≥ 90%; Time: 24H	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5%	PASS
E5	Aging test	GB /T 2423.2 - 2008 Temp: 80°C; Time: 24 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.≤5%	PASS
R1	RoHS	With Reference to IEC 62321:2008 with flow chart	Directive RoHS 2011/65/ EU	PASS
R2	PFOS	With Reference to USA EPA 3550C:1996 by LC/MS	Directive RoHS 2006/122/EC	PASS

RoHS

Compatible

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			



3	CR-113	1.13		1
2	CR-113-4	1.13		1
1	R-CB-113B	OD 1.13mm		1
NO.	Part Number	Description	Finished	Q'ty

TITLE:		OD1.13mm	
PART NO.:		IPEX1-IPEX4-0.5M	CUSTOMER P/N:
APP BY	CHK BY	RF BY	DES BY
LQ	DJC		DJC
2024-12-10	2024-12-10		2024-12-10
		UNITS: mm	Tolerance
		SCALE: 1/1	X.X ±0.5
		REVISION: A	X.XX ±0.2
			X° ±1°