

## Micro switch

## PRZ MSW34 R

### ◆ 安全可靠的中型开关 Safe, reliable basic switch

- 结构紧凑, 具有微小触点间隙, 快速动作、高灵敏和微小动作行程特点。  
Nice appearance, tight configuration. Characteristic: small contact gap, quick action, high sensitivity and small operating travel
- 长寿命, 高可靠: Long life, high reliability.
- 接线端子种类齐全: A variety of contact terminals
- 多种温度等级: A variety of temperature degree
- 动作力范围宽:  
A variety of models with low operating force to high operating force are available
- 采用热固性或热塑性塑料: Adopt thermosetting plastic or thermoplastic
- 配备各种形式动臂: A variety of levers
- 广泛应用于各种家用电器、电子设备、自动化设备、通讯设备、汽车电子、仪器仪表、电动工具等领域。  
Widely used in home appliance, electronic equipment, automatic machine, communication equipment, car electron, apparatus and instrument electric motion tool etc.

### ◆ 技术特性 Specifications

额定值/Rating	16 A	16A 125/250 or 480VAC 1/8HP 125VAC 1/4HP 250VAC 0.5A 125VDC 0.25A 250VDC
		16A 125/250VAC 5E4 $\mu$ 40T85
	22 A	22A 125/250 or 480VAC 1/4HP 125VAC 1/2HP 250VAC 0.5A 125VDC 0.25A 250VDC
		22A 125/250VAC 5E4 $\mu$ 40T85
	26 A	26A 125/250 or 480VAC 1/2HP 125VAC 1HP 250VAC 0.5A 125VDC 0.25A 250VDC
26A 250VAC 5E4 $\mu$ 40T85		
操作频率/Operating Frequency	电气/Electrical	10 ~ 30 次/分 cycles/min
	机械/Mechanical	240 次/分 cycles/min
触点电阻 (初始值) Contact Resistance (Initial Value)		50m $\Omega$ Max.
绝缘电阻/Insulation Resistance		100M $\Omega$ Min(at 500VDC)
抗电强度/Dielectric Strength	端子间/between terminals	1500VAC 50/60Hz 1min
	端子与外壳/between terminals and housing	2500VAC 50/60Hz 1min
环境温度/Storage Temperature		-40° C ~ +85° C
保存湿度/Storage Humidity		85%RH Max
寿命/Life	电气/Electrical	50,000 次 cycles or 100,000 次 cycles 取决于具体型号/Depends on Part No.
	机械/Mechanical	10,000,000 次 cycles

### ◆ 外形尺寸和动作特性 Dimensions and operating characteristics

