


Auto Flasher **WM FL016**

L×W×H(mm): 30.5×30.5×30



**Features**

- Failure indication;
- High sensitive and stable electronic timing;
- Suitable for flasher light during car turning;
- Wide operating voltage, temperature range and long life;
- Standard terminals, usage and Replacement easily.

**Ordering Information**

<b>WM FL016</b>			<b>- 12</b>	<b>- BJ</b>
<b>1</b>	<b>2</b>	<b>3</b>		
1 Part number: WM FL016			3 Failure indication: BJ: Failure indication;	
2 Rated Voltage(VDC): 12: 12V; 24: 24V			Nil: No Failure indication	

**Technical Characteristics**

Rated Voltage	12VDC, 24VDC
Operating Voltage	11VDC ~ 15VDC, 22VDC ~ 30VDC
Test Voltage	13VDC ± 0.2VDC, 26VDC ± 0.4VDC
Test Temperature	20°C±2°C
Switch Power	21W ~ 150W
Bulb failure warning	>140 times per minute
Flashing Frequency	60 ~ 120 times per minute
Duty Ratio	30% ~ 70%
Operating Temperature	-40°C ~ +80°C
Life	400 working hours
Weight(Approx.)	25g

**Layout (Bottom views, Unit: mm)**

<p><b>Dimensions</b></p>	<p><b>Wiring diagram(Bottom views)</b></p>
--------------------------	--