



- **Product Characteristics and Main Uses.**

NPNPN five layer silicon bidirectional device; Single side trenching technology with independent intellectual property rights, table glass passivation process; Multilayer metallized electrode on the back; High blocking voltage and high temperature stability;

Mainly used for: vacuum cleaners, power tools and other motor speed controller; solid state relays; heating controller (temperature control); other phase control circuit.



1.A1 2. A2 3.G  
TO-252(DPAK) top view

- **The limiting parameter**

Symbol	The name of the parameter			Values	Unit
$I_{T(RMS)}$	The through-state root - mean square current, the	BTA BTB	Tc=80°C Tc=90°C	12	A
$I_{TSM}$	On state inrush current	F=50HZ	t=20ms	80	A
$I^2t$	Limit value of $I^2t$	$t_p=10\text{ms}$		64	$\text{A}^2\text{s}$
$di/dt$	Critical rate of rise of on-state current		Tj=125	50	$\text{A}/\mu\text{s}$

$V_{DRM}/V_{RRM}$	Break-state repetition peak voltage inverse repetition peak voltage, the		$T_j=25^\circ C$	600/800	V
$I_{GM}$	peak gate current	$t_p=20\mu s$	$T_j=125^\circ C$	4	A
$P_{G(AV)}$	The average power dissipated at the gate pole, the		$T_j=125^\circ C$	1	W
$T_{STG} T_j$	storage temperature effective junction temperature			-40 to +150 -40 to +125	°C

- Electrical characteristics (three quadrants)

Symbol	name and test conditions	Quadrant		Values	Unit
$I_{GT}$	Trigger current $V_D=12V$ $R_L=100\Omega$ Trigger voltage	I II III	MAX	$\leq 50$	mA
$V_{GT}$			MAX	1.5	V
$V_{GD}$			MIN	0.2	V
$I_H$	Maintenanc e current $I_T=0.5A$	MAX		60	mA
$I_L$	Dynaflex $I_G=1.2I_{GT}$	MAX		60	mA
				100	
$dv/dt$	Critical rate of rise of off-state voltage $V_D=2/3V_{DRM}$ $T_j=125^\circ C$	MIN		500	V/us
$(dv/dt)c$	Critical rate of rise of commutation voltage $T_j=125^\circ C$	MIN		10	V/us

- Electrical characteristics (four quadrants)







Symbol	name and test conditions	Quadrant		Values	Unit
$I_{GT}$	Trigger current $V_D=12V$ $R_L=100\Omega$ Trigger voltage	I II III IV	MAX	I II III	mA
				$\leq 50$	
			MAX	$\leq 120$	
$V_{GT}$			MAX	1.5	V

$V_{GD}$	Non triggering voltage $T_j=125^\circ C$	MIN	0.2	V
$I_H$	Maintenance current $I_T=0.5A$	MAX	60	mA
$I_L$	Holding current $I_G=1.2I_{GT}$	MAX	60	mA
			100	
$dv/dt$	Critical rate of rise of off-state voltage $V_D=2/3V_{DRM} \quad T_j=125^\circ C$	MIN	500	V/us
$(dv/dt)_C$	Critical rate of rise of commutation voltage $T_j=125^\circ C$	MIN	10	V/us


- static parameters

Symbol	name and test conditions			Values	Unit
$V_{TM}$	On state peak voltage $ITM=16A$	$T_j=25^\circ C$	MAX	1.5	V
$V_{TO}$	threshold voltage	$T_j=125^\circ C$	MAX	0.86	V
$R_d$	slope resistance	$T_j=125^\circ C$	MAX	36.6	$m\Omega$
$I_{DRM} I_{RRM}$	peak off - state current reverse peak current	$T_j=25^\circ C$ $T_j=125^\circ C$	MAX	5	$\mu A$
				1	mA
$R_{th(j-c)}$	crust thermal resistance	BTA		2.05	$^\circ C/W$
		BTB		1.25	

● product characteristic curves



### Package Mechanical Data TO-252



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.10		2.50	0.083		0.098
A2	0		0.10	0		0.004
B	0.66		0.86	0.026		0.034
B2	5.18		5.48	0.202		0.216
C	0.40		0.60	0.016		0.024
C2	0.44		0.58	0.017		0.023
D	5.90		6.30	0.232		0.248
D1	5.30REF			0.209REF		
E	6.40		6.80	0.252		0.268
E1	4.63			0.182		
G	4.47		4.67	0.176		0.184
H	9.50		10.70	0.374		0.421
L	1.09		1.21	0.043		0.048
L2	1.35		1.65	0.053		0.065
V1		7°			7°	
V2	0°		6°	0°		6°

### Ordering information

Order code	Package	Baseqty	Deliverymode
UMW BT137S-600E	TO-252	2500	Tape and reel
UMW BT137S-800E	TO-252	2500	Tape and reel