


■ **DESCRIPTION**

The **ULN2804** is a high voltage, high current Darlington array comprised of eight NPN Darlington pairs. The device features open-collector outputs with suppression diodes for inductive loads and is ideally suited for interfacing between low-level logic circuitry and high power loads. Typical loads including relays DC motors, filament lamps, LED displays, printer hammers and high power buffers.


■ **FEATURE**

- * Eight Darlington pairs with common emitters
- * TTL, PMOS or CMOS Compatible inputs
- * Peak output current to 500mA
- * Output voltage to 50V
- * Clamp diodes for transient suppression
- * DIP-18 and SOP-18 packages


■ **MARKING**



■ **PIN CONFIGURATIONS**



■ **SCHEMATICS**



■ **ABSOLUTE MAXIMUM RATINGS**

PARAMETER	SYMBOL	RATINGS	UNIT
Input Voltage	V_{IN}	30	V
Output Voltage	V_{OUT}	50	V
Collector Current – Continuous	I_C	500	mA
Base Current – Continuous	I_B	25	mA
Power Dissipation	DIP-18	1.5	W
	SOP-18	0.95	W
Junction Temperature	T_J	+120	°C
Operating Ambient Temperature	T_{OPR}	0 ~ +70	°C
Storage Temperature	T_{STG}	-55 ~ +150	°C

Note Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied

■ **THERMAL DATA**

PARAMETER	SYMBOL	RATING	UNIT
Thermal resistance from junction to Ambient	DIP-18	60	°C /W
	SOP-18	80	°C /W

ELECTRICAL CHARACTERISTICS (Ta = 25°C, unless otherwise specified.)

PARAMETER	SYMBOL	TEST FIGURE	TEST CONDITIONS	MIN	TYP	MAX	UNIT	
Collector-Emitter Saturation Voltage	V _{CE(SAT)}	1	I _{OUT} =350mA, I _{IN} =500μA		1.3	1.6	V	
			I _{OUT} =200mA, I _{IN} =350μA		1.1	1.3	V	
			I _{OUT} =100mA, I _{IN} =250μA		0.9	1.1	V	
Input Voltage	V _{IN(ON)}	2	V _{CE} =2.0V	I _{OUT} =125mA		5.0	V	
				I _{OUT} =200mA		6.0	V	
				I _{OUT} =275mA		7.0	V	
				I _{OUT} =350mA		8.0	V	
Clamp Diode Forward Voltage	V _F	3	I _F =350mA		1.5	2.0	V	
Output Leakage Current	I _{CEX}	4a	V _{OUT} =50V, Ta=70°C			100	μA	
		4b	V _{OUT} =50V, Ta=70°C, V _{IN} =1.0V			500		
Input Current	ON	I _{IN(ON)}	5	V _{IN} =5V		0.35	0.5	mA
				V _{IN} =12V		1.0	1.45	mA
	OFF	I _{IN(OFF)}	6	I _{OUT} =500μA, Ta=70°C	50	100	μA	
Clamp Diode Reverse Current	I _R	7	V _R =50V, Ta=25°C			50	μA	
			V _R =50V, Ta=70°C			100	μA	
DC Current Gain	h _{FE}		V _{OUT} =2V, I _{OUT} =350mA	1000				
Input Capacitance	C _{IN}				15	25	pF	
Turn-On Delay	t _{ON}	8			0.25	1	μS	
Turn-Off Delay	t _{OFF}	8			0.25	1	μS	

■ **TEST FIGURES**

Figure 1.




Figure 2.




Figure 3.




Figure 4a.




Figure 4b.




Figure 5.




Figure 6.




Figure 7.






Figure 8.




Note1: Pulse width 50μs, duty cycle 10%
Output impedance 50Ω, $t_R \leq 5ns$, $t_F \leq 10ns$
Note2: $R_1 = 0$, $V_{IH} = 3V$
Note3: C_L includes probe and jig capacitance.

■ **TYPICAL CHARACTERISTICS**


Output Current vs. Saturation Voltage



Output Current vs. Input Current



Input Current vs. Input Voltage



Power Dissipation vs. Ambient Temperature

