## Technical Data 2110

Effective December 2017 Supersedes May 2014

# HTC PCB Fuse accessories for 5 mm fuses



BUSSMANN

## **PCB Fuse Blocks**

#### HTC-15M


-1.047" (26.6mm .354" (9.0mm) • 250 V, 6.3 A, 1.6 W HTC-140M Cover .571" • Tin plated brass terminals 14.5mr (5.5m • cURus: Guide IZLT2 & IZLT8, File # 14853 · Cover available: 531 Mounting Holes - HTC-150M (Transparent) - HTC-140M (Beige/Natural) 890" **←.866**"→ (22.0mm) (22 .177" (4.5mm .059" ± .002" Dia. (Typ.) (1.50 ± .05mm) -.**354"** (9.0mm) HTC-60M .591" (15.0mm) EP .551" .102" Dia. Hole (2.6mm) .051" Dia. Hole • 250 V, 6.3 A, 1.6 W (3.5mm) · Tin plated bronze terminals (1.3mm) .138" (3.5mm) PCB Fuse Clips .319 .50" (12.7m)


### HTC-200M


- Tin plated bronze
- · Tape and fan fold packed

## HTC-210M

Tin plated brass









Mounting Holes

.394"

S

.051" ± .002" Dia. (Typ.)

**.394**" (10.0mm)

Mounting Holes

(1.30 ± .05mm)

.051" ±

(1.30: .05 (10.0mm)

.002" Dia. (Typ.)

-1.303" (33.1mm

-1.303" (33.1mm

Printed Circuit Board

.461" Printed Circuit (11.7mm) Board

.461" (11.7mm)

Δ

## **PCB Fuse Holders**

#### HTC-45M

- 250 V, 10 A, 2.5 W
- . Bayonet cap/carrier
- Operating temperature range: -30 °C to + 85 °C ٠
  - nended replacement cURus: Guide IZLT2 & IZLT8 File + 1853

0

data sheet #

recommended for

#### HTC-50M

- . 250 V, 10 A, 2.5 W
- ٠ Bayonet cap/carrier
- Operating temperature range: -30 °C to + 85 °C
- cURus: Guide IZLT2 & IZLT8 File # 14853

#### **Common HTC specifications**

- Solerability: In accordance with IEC 68-2-20
- Molded materials: UL94 V-0 (HTC-15M UL94 V-1) ٠

Packaging Codes	
Packaging code prefix	Description
Blank	10 pieces packed into a carton (Not available on HTC-210M)
BK-	100 pieces packed into a cardboard shelf package
BK1-	1000 pieces packed into a poly bag
AP-	1000 pieces per box in Ammo pack (HTC-200M only)

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton Electronics Division 1000 Eaton Boulevard Cleveland, OH 44122 United States www.eaton.com/electronics



© 2017 Eaton All Rights Reserved Printed in USA Publication No. 2110 BU-MC17076 December 2017

Eaton is a registered trademark.

All other trademarks are property of their respective owners

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Eaton:

 BK/HTC-140M
 BK/HTC-10M
 BK/HTC-15M
 BK/HTC-70M
 BK/HTC-35M
 BK/HTC-40M
 BK/HTC-45M
 BK/HTC-35M

 150M
 BK/HTC-60M
 BK/HTC-50M
 BK/HTC-55M
 BK1-HTC-10M
 BK1-HTC-140M
 BK1-HTC-15M
 BK1-HTC-35M

 BK1-HTC-40M
 BK1-HTC-45M
 BK1-HTC-50M
 BK1-HTC-55M
 BK1-HTC-66M
 BK1-HTC-65M
 BK1-HTC-70M

 BK1/HTC-55M
 BK1/HTC-65M
 BK1/HTC-70M
 BK1/HTC-10M
 BK1/HTC-140M
 BK1/HTC-15M
 BK1/HTC-35M

 BK1/HTC-40M
 BK1/HTC-45M
 BK1/HTC-50M
 BK1/HTC-10M
 BK1/HTC-140M
 BK1/HTC-35M