



SY7208/SY7208B

High Efficiency 1MHz, 2A Step Up Regulator

General Description

The SY7208 and SY7208B are high efficiency boost regulators targeted for general step-up applications. SY7208B incorporates input over-voltage protection and turn off the regulator when the input voltage exceeds 7V.

Ordering Information

SY7208□(□□)□

- Temperature Code
C: - 40°C~85°C
- Package Code:
AB: SOT23-6
- Spec Code
None: 0.6 V_{REF}
B: 1V_{REF}

Features

- Wide input range: 3-25V bias input, 25Vout max
- 1MHz switching frequency
- Minimum on time: 100ns typical
- Minimum off time: 100ns typical
- Low Rdson: 0.2ohm
- Programmable softstart: SY7208B
- 7V input OVP protection: SY7208B
- RoHS Compliant and Halogen Free
- Accurate Reference:
 - o SY7208, 0.6V_{REF}
 - o SY7208B: 1V_{REF}
- Compact package: SOT23 6 pins

Applications

- WLED Drivers
- Networking cards powered from PCI or PCI-express slots

Typical Applications





Fig. 1 Typical Schematic Diagram



SY7208/SY7208B

Pinout (SOT23-6 top view)



Top Mark: CAxyz for SY7208 BLxyz for SY7208B

(Device code: CA for SY7208 and BL for SY7208B, *x=year code, y=week code, z= lot number code*)

| Pin Name | SOT23-6 | Pin Description |
|-----------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IN(SY7208) | 5 | Input pin. Decouple this pin to GND pin with 1uF ceramic cap. |
| IN1,2(SY7208B) | 6,5 | Input pins. Decouple this pin to GND pin with 1uF ceramic cap. |
| GND | 2 | Ground pin |
| LX | 1 | Inductor node. Connect an inductor between IN pin and LX pin. |
| FB | 3 | Feedback pin. Connect a resistor R1 between V _{OUT} and FB, and a resistor R2 between FB and GND to program the output voltage: V _{OUT} =0.6V*(R1/R2+1)—SY7208; V _{OUT} =1V*(R1/R2+1)—SY7208B. |
| SS (SY7208B) | 4 | External softstart pin. Add a capacitor to this pin to program the softstart time to limit the inrush current. For SY7208B, pull this pin to IN can disable the input OVP. |
| EN (SY7208) | 4 | Enable control. High to turn on the part. Don't leave it floated. |

Absolute Maximum Ratings (Note 1)

| | |
|---------------------------------------------------------------------------|----------------|
| OUT, LX, IN, SEN----- | 26V |
| All other pins----- | 6V |
| Power Dissipation, P _D @ T _A = 25°C SOT-23-6, ----- | 0.4W |
| Package Thermal Resistance (Note 2) | |
| θ _{JA} ----- | 250°C/W |
| θ _{JC} ----- | 130°C/W |
| Junction Temperature Range ----- | 150°C |
| Lead Temperature (Soldering, 10 sec.) ----- | 260°C |
| Storage Temperature Range ----- | -65°C to 150°C |
| ESD Susceptibility (Note 2) | |
| HBM (Human Body Mode) ----- | 2kV |
| MM (Machine Mode) ----- | 200V |

Recommended Operating Conditions (Note 3)

| | |
|----------------------------------|----------------|
| IN1,2, LX ----- | 3V to 25V |
| All other pins ----- | 0-5.5V |
| Junction Temperature Range ----- | -40°C to 125°C |
| Ambient Temperature Range ----- | -40°C to 85°C |



SY7208/SY7208B

Electrical Characteristics

(VIN = 5V, Vout=12V, Iout=100mA, TA = 25°C unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-----------------------------------|----------------------|-----------------|-------|-----|-------|------|
| Input Voltage Range | VIN | | 3 | 25 | | V |
| Quiescent Current | I _Q | FB=0.66V | | 100 | | μA |
| Shutdown Current (SY7208 only) | ISHDN | SY7208: EN=0 | | 1 | 5 | μA |
| Low Side Main FET RON | RDS(ON)1 | | | 200 | | mΩ |
| Main FET Current Limit | I _{LIM1} | | 2 | | 2.6 | A |
| Switching Frequency | F _{sw} | | 0.8 | 1 | 1.2 | MHz |
| Feedback Reference Voltage | V _{REF} | SY7208 | 0.588 | 0.6 | 0.612 | V |
| | | SY7208B | 0.98 | 1 | 1.02 | V |
| IN OVP rising threshold | V _{IN,OV} | SY7208B only | 7 | | | V |
| IN OVP hysteresis | V _{OV,HYS} | SY7208B only | | 0.3 | | V |
| IN UVLO rising threshold | V _{IN,UVLO} | | | | 2.7 | V |
| UVLO hysteresis | UVLO,HYS | | | 0.1 | | V |
| Thermal Shutdown Temperature | T _{SD} | | | 150 | | °C |

Note 1: Stresses listed as the above “Absolute Maximum Ratings” may cause permanent damage to the device. These are for stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may remain possibility to affect device reliability.



Note 2: θ_{JA} is measured in the natural convection at TA = 25°C on a low effective single layer thermal conductivity test board of JEDEC 51-3 thermal measurement standard.

Note 3: The device is not guaranteed to function outside its operating conditions.



SY7208/SY7208B

SOT23-6 Package outline & PCB layout design



Notes: All dimensions are in millimeters.

All dimensions don't include mold flash & metal burr.