



MATERIAL  
 HOUSING : HIGH TEMPERATURE HOUSING  
 NY-9T (UL94V-0) WITHSTANDS IR AND  
 VPR SOLDERING METHODS.  
 CONTACTS : PHOSPHOR BRONZE.  
 PLATING : SELECTIVE GOLD PLATED.

SPECIFICATION  
 CURRENT RATING : 1AMP.  
 INSULATOR RESISTANCE 5000MW MIN. AT DC 500V.  
 CONTACT RESISTANCE : 20MW MAX. AT DC 100mA.  
 OPERATING TEMPERATURE : -65°C ~ +125°C.  
 MAX PROCESSING TEMPERATURE: 230°C FOR 30~60 SECONDS.

SCREW DIMENSION OPTION

parts no.	DIM a	DIM b	inner thread
A	4.80	11.80	4#40
B	5.00	11.00	4#40
C			
D			
E			

<b>RoHS Compliant</b>		<b>HSM 玄茂科技股份有限公司</b> <b>HSUAN MAO TECHNOLOGY CO., LTD.</b>	
APPD. 核准 DWG. 製圖 HELEN DATE 制表日 2010/7/29	SCALE 比例 參考 UNIT 單位 MM PAGE 張數 1 OF 1	TOLERANCE XX ±0.30 ANG: ±3° X.XX ±0.20 X.XXX ±0.05 SIZE 紙張尺寸 A4 REV. 版本 A	PART NAME 品名 D-SUB PCB HD RIGHT ANGLE FOR NOTBOOK 15P FEMALE SMT TYPE RIVET 4-40 THREAD W/BOARDLOCK ,W/O LOCATING PEG NICKEL SHELL BLACK INSULATOR ROHS LOW-LEAD PART NO. 料號 C0524-15FCXNXBR