



CE



PCMB 2.5



Capability

Approval		
Standard	UL	IEC
Rated Voltage	300V	400V
Rated Current	20A	24A
Wire size	24-12AWG	0.2-2.5mm ²
T/W/End plate		5.2/28/1.5mm
Height _{mm} (NS35:7.5/NS35:15/NS32)		32mm
Rated Surge Voltage/Contamination Class		6KV/3
Stripping Length		8 mm
Screw Thread/Tightening Torque		M3/0.5N.m/4.5Lb-in
Internal Cylindrical Gage		A3
Insulating Material/Inflammability Class		PAV-0

Specification

	Model	Pieces
(1) Terminal Block	PCMB 2.5	50
(2) End Cover	D-PCMB2.5	50
(3) Fixed Bridge	FBR10-5N	10
(4) Step Bracket		
(5) Insertion Bridge	EB 10-5	10
(6) Isolator Bridge Bar, 10 P		
(7) Bridge Bar Isolator		
(8) Switching Bridge	SBRN 2-7	1
(9) Separating Plate	TS-KK 3	50
(10) Separating Plate, Width:1.5mm	ATP-PCMBK	50
(11) Test Plug Socket	PSB 3/10/4	100
(12) Test Plug Socket, Insulated		
(13) Zack Strip	ZB5	

HOW TO ORDER:

PCMB 2.5 — P — 1 —

Series No. No. of Pole Color Customer Request

1 Gray	4 Green	7 Trans-parent
2 Blue	5 Orange	8 Yellow
3 Black	6 Red	9 White

	 DEGSON ELECTRONICS CO., LTD.
	NAME PCMB 2.5